Resene ______Construction Systems

INTEGRA FLOORING SYSTEM

A 75mm thick, reinforced lightweight concrete flooring. Modern architectural trends and requirements for comfort and durability place tremendous demands on building structures. INTEGRA Flooring System offers the flexibility to meet these demands in a cost effective manner.

Proven Technology

Lightweight concrete flooring systems are a tried and tested method of flooring around the world. Incorporating the benefits of energy efficiency, insulation, acoustic qualities, and speed of installation to create a solid, flooring structure for in residential and light commercial buildings.

The INTEGRA Flooring System incorporates Aquapel infusion at manufacture for water repellancy throughout the entire panel including double steel mesh reinforcing. The panels are screw fixed into timber joists to ensure the strength, integrity and durability of the System.

Durable

This System carries a 25 year Product Performance Warranty when supplied and installed in accordance with our specifications creating a solid, durable flooring substrate you can trust.

Innovative design.
Integrated systems.
Enduring finish.





INTEGRA FLOORING SYSTEM

ROCCOTE | Plaster Systems.

System Features

- + Impact resistance
- + Acoustic benefits
- + Energy Efficient
- + Insulation
- + Speedy installation
- + Cost effective
- + Waterproof

Components:

- + INTEGRA LWC Floor Panels. (1800 × 600 × 75mm)
- + 14g x 100mm/150mm Galvanised INTEGRA Screws.

(100mm for fixing the Integra Floor Panels, and 150mm for perimeter of floor)


- + AAC Adhesive Bedding Compound.
- Resene Galvo-Prime Brush applied waterborne
 galvanised iron primer or
 Zinc rich spray pak primer.

Tools:

- + Broadknife.
- + Power saw with metal or diamond blade.
- Impact driver or standard drill with hex drive drill bit.
- + Safety Equipment. (Gloves, Earmuffs, Eyewear, Respiratory Protection)



0800 50 70 40 reseneconstruction.co.nz



Panel size

75mm x 1.800mm L x .600mm W

Weight

45.5 kg per panel / 520kg per m3 dry density

Compressive Strength 4mPa

Thermal resistance R 0.56

	INTEGRA Façade Light Weight Concrete	INTEGRA Flooring	INTEGRA Fencing	GRAPHEX Insulated Façade	GRAPHEX Masonry Overlay	GRAPHEX solid	Masonry Block	Fibre Cement	LiteRock	Brick	ICF(Polystyrene Blocks)	Tilt Panel	Artisan Interiors
Insulated	0	•		0	0	0					0		
Impact Resistance	0	•	0	0	0	0	0	0	0		0	0	
Acoustic	0	•	0			0			0	0	0	0	
Resene Colours	0		0	0	0		0	0	0	0	0	0	0
BRANZ	0			0	0	0	0	0	0				
Fire Tests	0	•		0	0	0	0	0	0	0	0	0	0
FPB	0	•	0	0	0	0	0	0	0	0	0	0	0
Full Render System	0		0	0	0	0	0	0	0	0	0		
Substrate supplied	0	•	0	0		0							
Acrylic Texture	0		0	0	0	0	0	0	0	0	0	0	
Mineral Texture	0		0	0	0	0	0		0	0	0	0	0
Cavity System	0			0				0	0				
GreenSite	0	•	0	0	0	0	0	0	0	0	0	0	
Masonry Construction	0	•	0		0	0	0			0	0	0	
Window Reveals	0		0	0	0	0	0			0	0	0	