ROCKCOTE PM100 RENDER

ROCKCOTE RESENE LTD TRADING AS RESENE CONSTRUCTION SYSTEMS

Version No: 2.4

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: **16/02/2022**Print Date: **16/02/2022**L.GHS.NZL.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
Product name	ROCKCOTE PM100 RENDER
Synonyms	Not Available
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions
itcicvant identified daes	Osc according to mandiacturer 3 directions

Details of the supplier of the safety data sheet

Registered company name	ROCKCOTE RESENE LTD TRADING AS RESENE CONSTRUCTION SYSTEMS
Address	32-50 VOGEL STREET LOWER HUTT New Zealand New Zealand
Telephone	+64 4 577 0500
Fax	+64 4 577 3327
Website	www.resene.co.nz
Email	Not Available

Emergency telephone number

• , .		
Association / Organisation	ROCKCOTE RESENE LTD TRADING AS RESENE CONSTRUCTION SYSTEMS	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	0800737363	+64 800 700 112
Other emergency telephone numbers	Not Available	+61 2 9186 1132

Once connected and if the message is not in your prefered language then please dial 01

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification ^[1]	Serious Eye Damage/Eye Irritation Category 1, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Skin Corrosion/Irritation Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.3A, 8.3A, 6.1E (respiratory tract irritant)

Label elements

Hazard pictogram(s)





Signal word Dang

Hazard statement(s)

H318	Causes serious eye damage.
H335	May cause respiratory irritation.
H315	Causes skin irritation.

Precautionary statement(s) Prevention

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves, protective clothing, eye protection and face protection.
P261	Avoid breathing dust/fumes.

Version No: **2.4** Page **2** of **9** Issue Date: **16/02/2022**

ROCKCOTE PM100 RENDER

Print Date: 16/02/2022

P264 Wash all exposed external body areas thoroughly after handling.

Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER/doctor/physician/first aider.
P302+P352	IF ON SKIN: Wash with plenty of water and soap.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362+P364	Take off contaminated clothing and wash it before reuse.

Precautionary statement(s) Storage

P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Ingredients are required by the Hazard Substances (Safety Data Sheets) Notice 2017, EPA consolidation 30 April 2021 to be identified:

Mixtures

CAS No	%[weight]	Name
65997-15-1	20-40	portland cement
14808-60-7.	40-80	graded sand
13463-67-7	1-10	titanium dioxide
1332-58-7	1-10	kaolin
Legend:	Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing for at least 15 minutes. Transport to hospital or doctor in event of irritation. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	If dust is inhaled remove from contaminated area.
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 Firefighting measures

Extinguishing media

- ▶ There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known.	
----------------------------------	--

Advice for firefighters

 Version No: 2.4 Page 3 of 9 Issue Date: 16/02/2022

ROCKCOTE PM100 RENDER

Print Date: 16/02/2022

Fire/Explosion Hazard

Non combustible. Decomposition may produce toxic fumes of: silicon dioxide (SiO2) metal oxides May emit poisonous fumes. May emit corrosive fumes.

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Use dry clean up procedures and avoid generating dust. Place in a suitable, labelled container for waste disposal.
Major Spills	Moderate hazard. Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear appropriate personnel protective equipment and clothing to prevent exposure. Avoid breathing in dust and skin or eyes contact_Sweep up or scrape up spilled material and place in suitable containers for recycle or disposal. Clean floor with large quantities of water to complete clean- up.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Avoid personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. When handling, DO NOT eat, drink or smoke.
Other information	► Store in original containers.

Conditions for safe storage, including any incompatibilities

Suitable container	► As supplied by manufacturer
Storage incompatibility	Calcium oxide: reacts violently with water, evolving high quantities of heat reacts violently, with acids, light metals, lithium, magnesium, powdered aluminium, phosphorus, potassium, sulphur trioxide Calcium sulfate: reacts violently with reducing agents is hygroscopic; reacts with water to form gypsum and Plaster of Paris

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA						
Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	portland cement	Portland cement	3 mg/m3	Not Available	Not Available	dsen-Dermal sensitiser
New Zealand Workplace Exposure Standards (WES)	portland cement	Portland cement respirable dust	1 mg/m3	Not Available	Not Available	dsen-Dermal sensitiser
New Zealand Workplace Exposure Standards (WES)	graded sand	Quartz respirable dust	0.05 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	titanium dioxide	Titanium dioxide	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	kaolin	Kaolin	10 mg/m3	Not Available	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	kaolin	Kaolin respirable dust	2 mg/m3	Not Available	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
graded sand	0.075 mg/m3	33 mg/m3	200 mg/m3

Version No: **2.4** Page **4** of **9** Issue Date: **16/02/2022**

ROCKCOTE PM100 RENDER

Print Date: **16/02/2022**

Ingredient	TEEL-1	TEEL-2		TEEL-3	
titanium dioxide	30 mg/m3	30 mg/m3 330 mg/m3		2,000 mg/m3	
Ingredient	Original IDLH	Original IDLH		Revised IDLH	
portland cement	5,000 mg/m3		Not Avail	able	
graded sand	25 mg/m3 / 50 mg/m3		Not Avail	able	
titanium dioxide	5,000 mg/m3		Not Avail	able	
kaolin	Not Available		Not Avail	able	

MATERIAL DATA

For kaolin:

Kaolin dust appears to have fibrogenic potential even in the absence of crystalline silica.

The concentration of respirable dust for application of this limit is to be determined from the fraction that penetrates a separator whose size collection efficiency is described by a cumulative lognormal function with a median aerodynamic volume of 4.0 um (+-) 0.3 um and with a geometric standard deviation of 1.5 um (+-) 0.1 um, i.e.. for calcium silicate:

containing no asbestos and <1% crystalline silica

ES TWA: 10 mg/m3 inspirable dust

TLV TWA: 10 mg/m3 total dust (synthetic nonfibrous) A4

Although in vitro studies indicate that calcium silicate is more toxic than substances described as 'nuisance dusts' is thought that adverse health effects which might occur following exposure to 10-20 mg/m3 are likely to be minimal.

NOTE: This substance has been classified by the ACGIH as A4 NOT classifiable as causing Cancer in humans

WARNING: For inhalation exposure ONLY: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS

The International Agency for Research on Cancer (IARC) has classified occupational exposures to respirable (<5 um) crystalline silica as being carcinogenic to humans .

Exposure controls

Exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
Personal protection	
Eye and face protection	 Safety glasses with side shields. Chemical goggles.
Skin protection	See Hand protection below
Hands/feet protection	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Rubber gloves
Body protection	Overalls
Respiratory protection	Particulate. Class P2 filter.

SECTION 9 Physical and chemical properties

Information on basic physical	and chemical properties		
Appearance	White powder		
Physical state	Solid	Relative density (Water = 1)	>1
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available BuAC = 1	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available

 Version No: 2.4
 Page 5 of 9
 Issue Date: 16/02/2022

 Print Date: 16/02/2022
 Print Date: 16/02/2022

ROCKCOTE PM100 RENDER

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	0
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (Not Available%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	0

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	▶ stable
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information	on	toxico	logical	effects
-------------	----	--------	---------	---------

	Inhaled	Inhalation may result in chrome ulcers or sores of nasal mucosa and lung damage.
Skin Contact Skin contact may result in severe irritation particularly to broken skin. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation. On the basis of epidemiological data, it has been concluded that prolonged inhalation of the material, in an occupational setting, may produce cancer in humans. Chronic Chronic Chronic Chronic May result in severe irritation particularly to broken skin. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects The basis of epidemiological data, it has been concluded that prolonged inhalation of the material, in an occupational setting, may produce cancer in humans. Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation. The health hazards associated with bentonite, kaolin, and common clay, which are commercially important clay products, as well as the related	Ingestion	May produce tissue injury similar to acid burns.
On the basis of epidemiological data, it has been concluded that prolonged inhalation of the material, in an occupational setting, may produce cancer in humans. Chronic Chr	Skin Contact	Skin contact may result in severe irritation particularly to broken skin.
cancer in humans. Chronic Ch	Еуе	When applied to the eye(s) of animals, the material produces severe ocular lesions which are present twenty-four hours or more after instillation.
·	Chronic	cancer in humans. Cement contact dermatitis (CCD) may occur when contact shows an allergic response, which may progress to sensitisation. The health hazards associated with bentonite, kaolin, and common clay, which are commercially important clay products, as well as the related

ROCKCOTE PM100 RENDER	TOXICITY Not Available	IRRITATION Not Available	
portland cement	TOXICITY Not Available	IRRITATION Not Available	
graded sand	TOXICITY Oral (Rat) LD50; 500 mg/kg ^[2]		IRRITATION Not Available
titanium dioxide	dermal (hamster) LD50: >=10000 mg/kg ^[2] Inhalation(Rat) LC50; >2.28 mg/l4h ^[1]	RRITATION Eye: no adverse effect obse Ekin (human): 0.3 mg /3D (ir Ekin: no adverse effect obse	nt)-mild *

lli	TOXICITY	IRRITATION
kaolin	Not Available	Not Available

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

PORTLAND CEMENT The following information refers to contact allergens as a group and may not be specific to this product.

Version No: **2.4** Page **6** of **9** Issue Date: **16/02/2022**

ROCKCOTE PM100 RENDER

Print Date: 16/02/2022

TITANIUM DIOXIDE	* IUCLID Exposure to the material may result in a possible risk of The material may produce moderate eye irritation lead The material may cause skin irritation after prolonged of WARNING: This substance has been classified by the	ing to inflammation. or repeated exposure and may produ	· · · · ·
KAOLIN	for bentonite clays: Bentonite (CAS No. 1302-78-9) consists of a group of clays formed by crystallisation of vitreous volcanic ashes that were deposited in water. The expected acute oral toxicity of bentonite in humans is very low (LD50>15 g/kg).		
ROCKCOTE PM100 RENDER & TITANIUM DIOXIDE	For titanium dioxide: Humans can be exposed to titanium dioxide via inhalation, ingestion or dermal contact.		
PORTLAND CEMENT & TITANIUM DIOXIDE	Asthma-like symptoms may continue for months or even years after exposure to the material ceases.		
PORTLAND CEMENT & GRADED SAND & TITANIUM DIOXIDE & KAOLIN	No significant acute toxicological data identified in literature search.		
Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

X − Data either not available or does not fill the criteria for classification
✓ − Data available to make classification

SECTION 12 Ecological information

DOGWOOTE DIMAG DENDED	Endpoint Test Duration (hr)		Species V		Value	Value		Source		
OCKCOTE PM100 RENDER	Not Available Not Available			Not Available	Not Available		Not Available			
	Endpoint		Test Duration (hr)		Species	Value		Source		
portland cement	Not Available Not Available				Not Available	Not Available		Not Available		
	Endpoint		Test Duration (hr)		Species	Value		Source		
graded sand	Not Available		Not Available		Not Available	Not Availa			Not Available	
	Endpoint	Те	est Duration (hr)	Species		Value	Value Source			
	BCF	1008h		Fish		<1.1-9.6		7		
	NOEC(ECx)	504h		Crustacea		0.02mg/l		4		
titanium dioxide	LC50	96h		Fish			1.85-3.06mg/l		4	
	EC50	72h		Algae or other aquatic plants		S	3.75-7.58mg/l		4	
	EC50	48h		Crustacea			1.9mg/l		2	
	EC50	96	Sh	Algae	or other aquatic plant	S	179.05mg/l		2	
	Endpoint		Test Duration (hr)		Species	Value		Source		
kaolin	Not Available		Not Available		Not Available	Not Availa	ble	Not Avai	lable	
Legend:	Extracted from 1. II	UCLID	Toxicity Data 2. Europe E	CHA Regisi	tered Substances - Ec	otoxicological Info	ormation - Aqua	atic Toxicity	4. US EPA	

Bentonite and kaolin have low toxicity to aquatic species, a large number of which have been tested **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
titanium dioxide	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
titanium dioxide	LOW (BCF = 10)

Mobility in soil

Version No: 2.4 Page 7 of 9 Issue Date: 16/02/2022 Print Date: 16/02/2022

ROCKCOTE PM100 RENDER

Ingredient	Mobility
titanium dioxide	LOW (KOC = 23.74)

SECTION 13 Disposal considerations

Waste treatment methods

Product / Packaging disposal

- DO NOTallow wash water from cleaning or process equipment to enter drains.
- ▶ Recycle wherever possible or consult manufacturer for recycling options.

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package.

Do not allow product or wash water from cleaning or process equipment to enter drains or watercourses. It may be necessary to collect all wash water for treatment before disposal. The generation of waste should be avoided or minimised wherever possible

Disposal of this product should comply with Hazard Substances (Disposal) Notice 2017 (EPA Consolidation 30 April 2021).

For treating and discharging processes contact your local authority.

SECTION 14 Transport information

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (UN): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
portland cement	Not Available
graded sand	Not Available
titanium dioxide	Not Available
kaolin	Not Available

Transport in bulk in accordance with the ICG Code

Transport in bank in acc	ranoport in bank in adder author that the fee data	
Product name	Ship Type	
portland cement	Not Available	
graded sand	Not Available	
titanium dioxide	Not Available	
kaolin	Not Available	

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002544	Construction Products Subsidiary Hazard Group Standard 2020

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

portland cement is found on the following regulatory lists

New Zealand Inventory of Chemicals (NZIoC)

graded sand is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Group 1: Carcinogenic to humans

New Zealand Approved Hazardous Substances with controls

titanium dioxide is found on the following regulatory lists

New Zealand Workplace Exposure Standards (WES)

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Version No: 2.4 Page 8 of 9 Issue Date: 16/02/2022

ROCKCOTE PM100 RENDER

Print Date: 16/02/2022

Chemical Footprint Project - Chemicals of High Concern List

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC

Monographs - Group 2B: Possibly carcinogenic to humans

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for

Manufactured Nanomaterials (MNMS)

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification

of Chemicals

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

kaolin is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantities
Not Applicable	Not Applicable

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
Not Applicable	Not Applicable	Not Applicable	Not Applicable	Not Applicable

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
New Zealand - NZIoC	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	16/02/2022
Initial Date	21/02/2017

SDS Version Summary

,		
Version	Date of Update	Sections Updated
1.4	15/02/2022	Chronic Health, Classification, Disposal, Physical Properties

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

ES: Exposure Standard

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value BCF: BioConcentration Factors

BEI: Biological Exposure Index

AIIC: Australian Inventory of Industrial Chemicals

Version No: 2.4 Page 9 of 9 Issue Date: 16/02/2022

ROCKCOTE PM100 RENDER

Print Date: 16/02/2022

DSL: Domestic Substances List NDSL: Non-Domestic Substances List

EICSC: Inventory of Existing Chemical Substance in China
EINECS: European INventory of Existing Commercial chemical Substances
ELINCS: European List of Notified Chemical Substances
NLP: No-Longer Polymers

ENCS: Existing and New Chemical Substances Inventory

KECI: Korea Existing Chemicals Inventory
NZIoC: New Zealand Inventory of Chemicals
PICCS: Philippine Inventory of Chemicals and Chemical Substances
TSCA: Toxic Substances Control Act
TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.